



Diesel Powered Generating Sets Power By Cummins Engine

DIY-C355,50HZ,230/400V,3P/4W

Standard Genset Features Generator Performance Generator Set Options

Single Source Responsibility

Design, manufacture and testing of engine, alternator, control system and complete generating set are all produced by the companies with DIY Group.

Single bearing alternator, class H/H
Standard voltage 230/400 volts 50 Hz
Exciter/Voltage reg - Torque Match as standard
Standard ComAp AMF20 Auto start whith AMF
Steel base frame with A/V mounting,
Engine, Alternator, Chassis & Control Box
3 pole Delixi Circuit Breaker
50 Degree Radiator
Packing under shrunk plastic film
Operation & Maintenance manual
Standard set of labels
Battery Charger 24V, 5A or 10A
Floating Battery Charger 24V, 5A or 10A
Seaworthy Plastic film packaging
Maintenance-free battery

Voltage Regulation

Maintains voltage output to within $\pm 1.0\%$.
At any power factor between 0.8 and 1.0
At any variations from No load to Full load.
At any variations from Cold to Hot.
At speed droop variations up to 4.5%.

Frequency Regulation

Isochronous under varying loads from no load to 100% full load when electronic governor is fitted

Random Frequency Variation

Will not exceed $\pm 0.25\%$ of its mean value for constant loads – no load to full load.

Waveform

Total harmonic distortion open circuit voltage waveform in the order of 1.8%. Three-phase balanced load in the order of 5.0%.

Telephone Influence Factor (TIF)

TIF better than 50.
THF to BS 4999 Part 40 better than 2%.

Alternator Temperature Rise

Class H insulation.

Radio Interference

In compliance with BS 800 and VDE levels G and N.

Fuel options

Fuel Tank under 8working hours capacity

Exhaust Options

Exhaust Silencer - Industrial In-Line
Exhaust Bellows
Exhaust Silencer - Residential , In-Line
Installation Kit - Industrial Silencer
Installation Kit - Residential Silencer

Voltage Connections

240/416V, 230/400V, 220/380V,

Miscellaneous Options

3 pole or 4 pole Circuit Breaker
Optional Set mounted starting batteries
Coolant Heater 240V
Battery Charger 240V, 5A or 10A
Automatic Transfer Switches
Packing - Export Box

Engine Specification Alternator Specification Quality Standards

Type

Cummins water cooled Diesel engine, four cycle, turbocharged and low temperature aftercooled

Construction

Two valves per cylinder, forged steel crankshaft and connecting rods, cast iron block.

Starting

12/24 volt negative earth. Battery charging alternator 35 amp on engine. Cranking current 1800 amps at 0°C.

Fuel System

12/24 volt fail safe actuator. Spin-on paper element fuel filters with fuel pump injection system with integral electronic governor. Dual flexible fuel lines and connectors. Standard fuel water separator.

Filters

Air cleaner with dry element.
Spin-on full flow lube oil filter.

Cooling

40°C ambient temperature standard
Stone guard. Drain Tap

Type

Brushless single bearing, revolving field, pole, drip proof, screen protected.
Class H Insulation, IP23 Protection
Fully interconnected damper winding.
AC exciter and rotating rectifier unit.
Epoxy coated stator winding.
Rotor and exciter impregnated with tropical grade insulating oil and acid resisting polyester resin. Dynamically balanced rotor BS 5625 grade 2.5.
Sealed for life bearings.
Layer wound mechanically wedged rotor.

Exciter

Triple dipped in moisture, oil and acid resisting polyester varnish and coated with anti-tracking varnish.

Output windings with 2/3 pitch for improved harmonics and paralleling ability.

Close coupled engine/alternator for perfect alignment.

To BS4999/5000 pt 99,
VDE 0530, UTE5100,
NEMA MG1-22, CEMA,
IEC 34, CSA A22.2,
AS1359, BS 5514,
ISO 3046 and ISO 8528
ISO9001:2000,ISO14000,
CE Compliance



Engine Performance Data@1500RPM				
Output Power	Fuel Consumption			
	%	kW	g/kW.h	L/h
Standby Power				
110	321	207	79	
Prime Power				
100	292	201	69	
75	219	202	52	
50	146	200	34	
25	73	214	18	

Specification

Model	DIY-C355	Alternator Manufacture	LeroySomer
Standby Power	355kVA/284kW	Alternator Model	LSA4602L12
Prime Power	325kVA/260kW	Standby Power	327kVA/262kW
Engine Manufacture	CCEC CUMMINS	Prime Power	315kVA/252kW
Engine Model	Cummins QSM11-G2	Alternator Voltage Regulation	AVR R250
Number of Cylinders	6L	Alternator Insulation	H
Air intake way	Turbocharged and Charge Air Cooled	Protection Class	IP23
Borestroke	125mm X 147mm	Fuel Consumption at 100% Output (Standby)	79L/h
Compression Ratio	16.3:1	Fuel Consumption at 100% Output (Prime)	69L/h
Displacement	10.8L	Intake Air Flow	378L/Sec
Engine Standby Output	321KW(50HZ)	Exhaust Gas Temperature(Standby)	563°C
Engine Prime Output	292kW	Radiated Heat to Ambient(Standby)	43
Speed	1500 rpm	Fuel Tank Capacity	632L/167Gallon(Open Type)
Lubrication Capacity	34 liter	Coolant Capacity	10 liter

In accordance with ISO 8528, 3046, BS5514

PRIME POWER

Prime Power is available continuously during the period of power outage in a variable load application. Variable load should not exceed a 70% average of the prime power rating




during any 24 hour period.

A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation.

STANDBY POWER

The Standby Power is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Canopy diagram



1500 rmp400v 3P 4W/60HZ/0.8F			Open type Dimensions & Weight				Canopy type Dimensions & Weight			
Genset Model	Cummins	Original Stamford	Length mm	Width mm	Height mm	Weight(dry) kg	Length mm	Width mm	Height mm	Weight(dry) kg
DIY-C313R5	NTA855G1A	HCI444D	2570	1160	1680	2980	4650	1600	2260	5200
DIY-C350R5	NTA855G1B	HCI444ES	3050	1150	1760	4020	4650	1600	2260	5200
DIY-C450R5	NTAA855G7A	HCI444F	3440	1430	2100	5200	4650	1600	2260	5200

Robust Corrosion Resistant Construction

- Δ Black finish stainless stell lock and hinges
- Δ body made from steel components treated with polyester powder coating

Excellent Access for Maintenance

- Δ radiator fill access plate
- Δ lube oil and cooling water drains pipes to exterior of the enclosure
- Δ adding cooling water from top of canopy
- Δ LED light will be lighting automatically when open the door

Security and Safety

- Δ control panel viewing window in a lockable access door
- Δ emergency stop push button (red)mounted on enclosure interior
- Δ cooling fan and battery charging alternator fully guarded
- Δ exhaust silencing system totally enclosed for operator safety
- Δ Control panel and cable design in different directions,all the connection wiring in control panel are more neater and firmer.

Note:

Rating Definitions (Operation at Altitude ≤1000m, Ambient temperature ≤ 40°C)Continuous Power.These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

Control Panel -ComAp

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- a) Instruments: V, A (3 phase), Hz, kW, kVAr, kWh.
- b) Controls: Push buttons and LEDs for simple control.
- c) Control module: Standard collocation is ComAp AMF20 Auto start with AMF.

Main Features:

- Δ Support of engines equipped with Electronic Control Unit J1939 interface (25) 1
- Δ Remote Start operation available
- Δ Active SMS / E-mails
- Δ Comprehensive diagnostic messages; SPN / FMI codes; KWP2000 support
- Δ Automatic or manual start / stop of the gen-set
- Δ Graphic back-lit LCD display
- Δ Parameters adjustable via keyboard or PC
- Δ Selectable protections alarm / shutdown
- Δ Configurable analog inputs and outputs
- Δ Battery voltage, engine speed (pickup) measurement
- Δ Configurable programmable binary inputs and outputs
- Δ Event based history file
- Δ Warm-up and cooling functions
- Δ Generator C.B. and Mains C.B. control with feedback and return timer
- Δ Power and temperature switching binary output
- Δ Wide range of communication interfaces



**ISO
9001
QUALITY
ASSURANCE**

DIY reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data

See your distributor for more information.



**LERROY
SOMER**

